



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/799,707	03/15/2004	Hidenori Shindoh	250438US2	8967

22850 7590 12/31/2009
OBLON, SPIVAK, MCCLELLAND MAIER & NEUSTADT, L.L.P.
1940 DUKE STREET
ALEXANDRIA, VA 22314

EXAMINER

HANG, VU B

ART UNIT	PAPER NUMBER
----------	--------------

2625

NOTIFICATION DATE	DELIVERY MODE
-------------------	---------------

12/31/2009

ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

patentdocket@oblon.com
oblonpat@oblon.com
jgardner@oblon.com

Office Action Summary	Application No. 10/799,707	Applicant(s) SHINDOH ET AL.	
	Examiner Vu B. Hang	Art Unit 2625	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 18 September 2009.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-12 and 14-28 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-12 and 14-28 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 15 March 2004 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

- This office action is responsive to the communication filed on 09/18/2009.
- The amendments received on 09/18/2009 have been entered and made of record.
- Claims 1-12 and 14-28 have been entered and made of record.

Response to Arguments

1. Applicant's arguments filed on 09/18/2009 have been fully considered but they are not persuasive. The applicant argues that the cited prior art references, Endo (US Patent 6,801,340 B1), Mori (US Patent 6,965,453 B1), and Yasunobu (US Patent 7,046,394 B2), fails to disclose wherein the control unit includes "a plurality of registers configured to store a conversion passcode, the control unit selecting one or more conversion units in accordance with the passcode stored in the plurality of registers." In response, the examiner points out that Endo discloses a control unit configured to control the conversion units, and configured to output and receive the image data to/from the data communication bus (see Fig.2 (211,205,207,208,209,210), Fig.3 (308) and Col.5, Line 45-53). Endo further teaches that the conversion units are selected in accordance to the document data type and destination information (see Fig.3 (302,305,308), Fig.7 (701,705) and Col.5, Line 21-58); and discloses wherein the control unit selects one of the conversion units according to the request so as to make the selected one of the conversion units convert the image data (see Fig.3 (302,308), Fig.9 (\$909) and Col.6, Line 46-51). At the time of the invention, it would have been obvious for one skilled in the art to use to store and use the passcodes representing the data type information and/or destination information for selecting the conversion units. The motivation would be to use

Art Unit: 2625

a computer instruction codes for controlling the control unit to make the conversion unit selections.

Claim Rejections - 35 USC § 103

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

3. Claims 1-2, 5 and 12-28 are rejected under 35 U.S.C. 103(a) as being unpatentable over Endo (US Patent 6,801,340 B1) in view of Mori (US Patent 6,965,453 B1), and in further view of Yasunobu (US Patent 7,046,394 B2).

4. Regarding **Claim 1**, Endo discloses an electronic device which receives image data across a data communication bus shared among a memory, a processing unit and the electronic device, and converts the image data for outputting therefrom (see Fig.2 (211,201,203,205), Fig.3 (305,308), Col.3, Line 28-44 and Col.3, Line 57-66), comprising: a plurality of conversion units configured to convert the image data (see Fig.3 (308), Col.5, Line 30-34 and Col.6, Line 33-36); a control unit configured to control the conversion units, and configured to output and receive the image data to/from the data communication bus (see Fig.2 (211,205,207,208,209,210), Fig.3 (308) and Col.5, Line 45-53); an image data transfer unit configured to transfer the image data between the control unit and at least two of the conversion units (see Fig.3 (302), Col.5, Line 30-34 and Col.5, Line 45-53). Endo fails to disclose a clock unit configured to provide synchronization between the control unit and at least two of the conversion units for transfer of

Art Unit: 2625

image data; and a plurality of registers configured to store a conversion passcode, wherein the control unit selecting one or more conversion units in accordance with the passcode stored in the plurality of registers, and wherein the image data is transferred via the data communication bus between the memory and the control unit a first time before the conversions by the at least two conversion units and a second time after completion of the conversions by the at least two conversion units.

5. Endo, however, discloses a working memory unit for storing input document data, and performing image data format conversion and transmission to a plurality of destinations (see Fig.2 (203,205), Fig.4, Col.3, Line 48-52 and Col.4, Line 38-48). Endo also discloses a control unit configured to control the conversion units, and configured to output and receive the image data to/from the data communication bus (see Fig.2 (211,205,207,208,209,210), Fig.3 (308) and Col.5, Line 45-53); and teaches that the conversion units are selected in accordance to the document data type and destination information (see Fig.3 (302,305,308), Fig.7 (701,705) and Col.5, Line 21-58). Mori discloses an image processor for printing image data (see Fig. 1 and Col.4, Line 35-41), wherein the image processor includes a first conversion unit for converting image data into a format based on its initial compression format (see Fig. 1 (22) and Col.6, Line 31-37), a second conversion unit for converting the color format of the image data into a second color format (see Fig. 1 (33) and Col.7, Line 30-37), and a clock unit configured to provide synchronization between the control unit and the two conversion units for transfer of image data (see Fig.1 (30,22,27,33), Col.5, Line 15-30, Col.5, Line 55-59 and Col.6, Line 4-18). Yasunobu discloses an electronic device for converting image data into a suitable format for transmission (see Fig. 1, Fig.3 and Col.4, Line 38-47), wherein the image data is transferred between the

Art Unit: 2625

memory and the control unit a first time before the conversions by the at least two conversion units and a second time after completion of the conversions by the at least two conversion units (see Fig.2 (20,21, 23,27,32,33,34), Col.7, Line 2-10 and Col.7, Line 54 - Col.8, Line 3). [Note: The input image data is stored into the data storage unit 21 of Figure 2 via central controller 20 for image processing. The data conversion management unit 33 and the format converter 34 convert the input image data into the appropriate format and stores the image data back into data storage unit 21 before the image transmission process.]

6. Endo, Mori and Yasunobu are combinable because they are from the same field of endeavor, namely image data processing systems. At the time of the invention, it would have been obvious for one skilled in the art to include to Endo's device a clock unit configured to provide synchronization between the control unit and at least two of the conversion units for transfer of image data, wherein the control unit outputs the image data after a predetermined number of conversions are completed by the conversion units. The motivation would be to convert the image data into a suitable output format for printing, and to regulate the transmission of image data to the image conversion units at a predetermined rate. The compression format and the color format of the image data would allow for the image data to be printed at a specific outputting device. The synchronizing clock unit can ensure a steady flow of image data to the conversions units for processing efficiency. It is further obvious for one skilled in the art to configure the electronic device to transfer the image data via the data communication bus between the memory and the control unit a first time before the conversions by the at least two conversion units and a second time after completion of the conversions by the at least two conversion units. The motivation would be to store the processed image data into memory for

Art Unit: 2625

image transmissions. The stored and processed image data could be used for retransmissions or transmission to another device, without having to repeat the conversion process on the image data. It is also obvious for one skilled in the art to include to the control unit a plurality of registers configured to store a conversion passcodes representing the data type information and/or destination information for selecting the conversion units. The motivation would be to use a computer instruction codes for controlling the control unit to make the conversion unit selections.

7. Regarding **Claim 2**, Endo further discloses wherein the control unit supplies to one of the conversion units a signal (command) indicative of a start of transfer of the image data when transferring the image data to one of the conversion units (see Fig.3 (302,308), Fig.9 (\$907,\$909) and Col.5, Line 45-50).

8. Regarding **Claim 5**, Endo further discloses wherein one of the conversion units supplies to the control unit a signal (command) indicative of a start of transfer of the converted image data to the control unit for transmitting the converted image data to a designated receiver unit (see Fig.3 (302,305,308,309) and Col.5, Line 53-56).

9. Regarding **Claim 12**, Endo further discloses wherein the control unit makes one of the conversion units convert the image data according to a request indicative of a conversion that is applied to the image data (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35).

10. Regarding **Claim 14**, Endo further discloses wherein the request specifies a format of the image data prior to conversion and a format of the converted image data (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35).

Art Unit: 2625

11. Regarding **Claim 15**, Mori further discloses a clock unit is configured for transferring the image data between the control unit and one of the conversion units at a constant rate (see Fig. 1 (30,22,27,33), Col.5, Line 15-30, Col.5, Line 55-59 and Col.6, Line 4-18).

12. Regarding **Claim 16**, an official notice is taken that it is known in the art that a processing hardware unit of a computer system are implemented with a program stored in a computer chip.

13. Regarding **Claim 17**, an official notice is taken that it is known in the art that the processing functions of the hardware of an image processing computer system are implemented on printed circuit boards that are connectable to an upper-order apparatus such as a scanner unit or a multifunction peripheral device.

14. Regarding **Claim 18**, Endo further discloses wherein the image data is received from the upper-order apparatus, and the converted image data is output to the upper-order apparatus (see Fig.3 (302,305,308,309) and Col.4, Line 22-28).

15. Regarding **Claim 19**, Endo further discloses wherein the control unit is also configured to convert the image data (see Fig.3 (308) and Col.5, Line 45-53).

16. Regarding **Claim 20**, Endo discloses an image forming apparatus (see Fig.3, Col.3, Line 28-44 and Col.3, Line 57-66), comprising: hardware resources configured to form images (see Fig.2 and Col.3, Line 28-44); a memory having a program stored therein for causing the hardware resources to form the images (see Fig.2, Col.3, Line 28-44 and Col.8, Line 39-43); a central processing unit (see Fig.2 (201)); a data communication bus shared among the memory, the processing unit and the electronic device (see Fig.2 (211,201,203,205)); and an electronic device which receives image data, and converts the image data for outputting therefrom (see

Art Unit: 2625

Fig.3 (305,308), Col.3, Line 28-44 and Col.3, Line 57-66), comprising: a plurality of conversion units configured to convert the image data (see Fig.3 (308), Col.5, Line 30-34 and Col.6, Line 33-36); a control unit configured to control the conversion units, and configured to output and receive the image data to/from the data communication bus (see Fig.2

(211,205,207,208,209,210), Fig.3 (308) and Col.5, Line 45-53); an image data transfer unit is configured to transfer the image data between the control unit and at least two of the conversion units (see Fig.3 (302), Col.5, Line 30-34 and Col.5, Line 45-53). Endo fails to disclose a clock unit configured to provide synchronization between the control unit and at least two of the conversion units for transfer of image data; and a plurality of registers configured to store a conversion passcode, wherein the control unit selecting one or more conversion units in accordance with the passcode stored in the plurality of registers, and wherein the image data is transferred via the data communication bus between the memory and the control unit a first time before the conversions by the at least two conversion units and a second time after completion of the conversions by the at least two conversion units.

17. Endo, however, discloses a working memory unit for storing input document data, and performing image data format conversion and transmission to a plurality of destinations (see Fig.2 (203,205), Fig.4, Col.3, Line 48-52 and Col.4, Line 38-48). Endo also discloses a control unit configured to control the conversion units, and configured to output and receive the image data to/from the data communication bus (see Fig.2 (211,205,207,208,209,210), Fig.3 (308) and Col.5, Line 45-53); and teaches that the conversion units are selected in accordance to the document data type and destination information (see Fig.3 (302,305,308), Fig.7 (701,705) and Col.5, Line 21-58). Mori discloses an image processor for printing image data (see Fig. 1 and

Art Unit: 2625

Col.4, Line 35-41), wherein the image processor includes a first conversion unit for converting image data into a format based on its initial compression format (see Fig. 1 (22) and Col.6, Line 31-37), a second conversion unit for converting the color format of the image data into a second color format (see Fig. 1 (33) and Col.7, Line 30-37), and a clock unit configured to provide synchronization between the control unit and the two conversion units for transfer of image data (see Fig. 1 (30,22,27,33), Col.5, Line 15-30, Col.5, Line 55-59 and Col.6, Line 4-18). Yasunobu discloses an electronic device for converting image data into a suitable format for transmission (see Fig. 1, Fig.3 and Col.4, Line 38-47), wherein the image data is transferred between the memory and the control unit a first time before the conversions by the at least two conversion units and a second time after completion of the conversions by the at least two conversion units (see Fig.2 (20,21, 23,27,32,33,34), Col.7, Line 2-10 and Col.7, Line 54 - Col.8, Line 3). [Note: The input image data is stored into the data storage unit 21 of Figure 2 via central controller 20 for image processing. The data conversion management unit 33 and the format converter 34 convert the input image data into the appropriate format and stores the image data back into data storage unit 21 before the image transmission process.]

18. Endo, Mori and Yasunobu are combinable because they are from the same field of endeavor, namely image data processing systems. At the time of the invention, it would have been obvious for one skilled in the art to include to Endo's device a clock unit configured to provide synchronization between the control unit and at least two of the conversion units for transfer of image data, wherein the control unit outputs the image data after a predetermined number of conversions are completed by the conversion units. The motivation would be to convert the image data into a suitable output format for printing, and to regulate the transmission

Art Unit: 2625

of image data to the image conversion units at a predetermined rate. The compression format and the color format of the image data would allow for the image data to be printed at a specific outputting device. The synchronizing clock unit can ensure a steady flow of image data to the conversions units for processing efficiency. It is further obvious for one skilled in the art to configure the image forming apparatus to transfer the image data via the data communication bus between the memory and the control unit a first time before the conversions by the at least two conversion units and a second time after completion of the conversions by the at least two conversion units. The motivation would be to store the processed image data into memory for image transmissions. The stored and processed image data could be used for retransmissions or transmission to another device, without having to repeat the conversion process on the image data. It is also obvious for one skilled in the art to include to the control unit a plurality of registers configured to store a conversion passcodes representing the data type information and/or destination information for selecting the conversion units. The motivation would be to use a computer instruction codes for controlling the control unit to make the conversion unit selections.

19. Regarding **Claim 21**, Endo further discloses a conversion request generating unit which generates a conversion request, wherein the electronic device converts the image data in response to the conversion request (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35).

20. Regarding **Claim 22**, Endo further discloses a conversion type specifying unit which generates information about a format of the image data prior to conversion and a format of the image data after the conversion (see Fig.4 and Col.4, Line 38-48), the information being supplied to the conversion request generating unit (see Col.6, Line 18-28 and Col.6, Line 33-35).

Art Unit: 2625

21. Regarding **Claim 23**, Endo further discloses wherein the request generating unit generates the conversion request responsive to the information supplied to the from the conversion type specifying unit (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35).

22. Regarding **Claim 24**, Endo further discloses a memory area allocating unit which allocates a memory area in which the image data to be converted by the electronic device and the converted image data are stored (see Fig.2 (203) and Col.3, Line 32-44).

23. Regarding **Claim 25**, Endo discloses a method of converting image data by use of a plurality of conversion units configured to convert the image data, a control unit configured to control the conversion units (see Fig.3 (305,308), Col.3, Line 28-44 and Col.3, Line 57-66), and a data communication bus shared among a memory, a processing unit, and the control unit (see Fig.2 (211,201,203,205)), comprising the steps of: receiving image data from the communication bus into the control unit (see Fig.2 (211,101,207,208,209,210)); notifying the control unit of a type of conversion that is to be performed with respect to the image data (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35); selecting, by the control unit, one of the conversion units in response to the notified type of conversion (see Fig.3 (302,308), Fig.9 (\$909) and Col.6, Line 46-51); supplying, from the control unit, to the multiple conversion units, a signal (command) indicative of a start of transfer of the image data (see Fig.3 (302,308), Fig.9 (\$907,\$909) and Col.5, Line 45-50); and transferring the image data from the control unit to the conversion units (see Fig.3 (302,308), Fig.9 (\$907,\$909) and Col.5, Line 45-50). Endo fails to disclose selecting at least two conversion units in response to a notified type of conversion; supplying, from the control unit to the selected conversion units, a clock signal that provides

Art Unit: 2625

synchronization for transfer of the image data; storing in a plurality of registers passcodes indicating the types of conversion; and outputting the image data is transferred via the data communication bus between the memory and the control unit a first time before the conversions by the at least two conversion units and a second time after completion of the conversions by the at least two conversion units.

24. Endo, however, discloses a working memory unit for storing input document data, and performing image data format conversion and transmission to a plurality of destinations (see Fig.2 (203,205), Fig.4, Col.3, Line 48-52 and Col.4, Line 38-48). Endo also discloses a control unit configured to control the conversion units, and configured to output and receive the image data to/from the data communication bus (see Fig.2 (211,205,207,208,209,210), Fig.3 (308) and Col.5, Line 45-53); and teaches that the conversion units are selected in accordance to the document data type and destination information (see Fig.3 (302,305,308), Fig.7 (701,705) and Col.5, Line 21-58). Mori discloses an image processor for printing image data (see Fig. 1 and Col.4, Line 35-41), wherein the image processor includes a first conversion unit for converting image data into a format based on its initial compression format (see Fig. 1 (22) and Col.6, Line 31-37), a second conversion unit for converting the color format of the image data into a second color format (see Fig. 1 (33) and Col.7, Line 30-37), and a clock unit configured to provide synchronization between the control unit and the two conversion units for transfer of image data (see Fig. 1 (30,22,27,33), Col.5, Line 15-30, Col.5, Line 55-59 and Col.6, Line 4-18). Yasunobu discloses an electronic device for converting image data into a suitable format for transmission (see Fig.1, Fig.3 and Col.4, Line 38-47), wherein the image data is transferred between the memory and the control unit a first time before the conversions by the at least two conversion

Art Unit: 2625

units and a second time after completion of the conversions by the at least two conversion units (see Fig.2 (20,21, 23,27,32,33,34), Col.7, Line 2-10 and Col.7, Line 54 - Col.8, Line 3). [Note: The input image data is stored into the data storage unit 21 of Figure 2 via central controller 20 for image processing. The data conversion management unit 33 and the format converter 34 convert the input image data into the appropriate format and stores the image data back into data storage unit 21 before the image transmission process.]

25. Endo, Mori and Yasunobu are combinable because they are from the same field of endeavor, namely image data processing methods. At the time of the invention, it would have been obvious for one skilled in the art to include to Endo's method of converting image data the steps for selecting at least two conversion units in response to a notified type of conversion; supplying, from the control unit to the selected conversion units, a clock signal that provides synchronization for transfer of the image data; and outputting the image data to the communication bus after image data conversions by at least two data conversion units. The motivation would be to convert the image data into a suitable output format for printing in accordance to the type of processing that is to be performed with respect to the image data, and to regulate the transmission of image data to the image conversion units at a predetermined rate. The compression format and the color format of the image data would allow for the image data to be printed at a specific outputting device, based on the type of image data received from the input device. The synchronizing clock unit can ensure a steady flow of image data to the conversions units for processing efficiency. It is further obvious for one skilled in the art to include the steps for outputting the image data via the data communication bus between the memory and the control unit a first time before the conversions by the at least two conversion

Art Unit: 2625

units and a second time after completion of the conversions by the at least two conversion units.

The motivation would be to store the processed image data into memory for image transmissions. The stored and processed image data could be used for retransmissions or transmission to another device, without having to repeat the conversion process on the image data. It is also obvious for one skilled in the art to include the step for storing in a plurality of registers passcodes indicating the types of conversion. The motivation would be to use a computer instruction codes for controlling the control unit to make the conversion unit selections.

26. Regarding **Claim 26**, the rationale provided for the rejection of Claim 25 is incorporated herein.

27. Regarding **Claim 27**, Endo discloses a method of converting image data by use of a plurality of conversion units configured to convert the image data (see Fig.3 (305,308), Col.3, Line 28-44 and Col.3, Line 57-66), a data communication bus shared among a memory, a processing unit, and the control unit (see Fig.2 (211,201,203,205)), the control unit configured to control the conversion units (see Fig.3 (308) and Col.5, Line 45-53), and a conversion request generating unit configured to request conversion (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35), comprising the steps of: receiving image data from the communication bus into the control unit (see Fig.2 (211,101,207,208,209,210)); generating, by the conversion request generating unit, information about the type of conversion that is to be performed with respect to the image data (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35); instructing, by the conversion request generating unit, the control unit to perform the conversion based on the information (see Fig.3 (302,308), Fig.9 (\$909) and Col.6, Line 46-51); selecting, by

Art Unit: 2625

the control unit, one of the conversion units in response to the notified type of conversion (see Fig.3 (302,308), Fig.9 (\$909) and Col.6, Line 46-51); supplying, from the control unit to the conversion units, a signal (command) indicative of a start of transfer of the image data (see Fig.3 (302,308), Fig.9 (\$907,\$909) and Col.5, Line 45-50); and transferring the image data from the control unit to the conversion units (see Fig.3 (302,308), Fig.9 (\$907,\$909) and Col.5, Line 45-50). Endo fails to disclose selecting at least two conversion units in response to a notified type of conversion; supplying, from the control unit to the selected conversion units, a clock signal that provides synchronization for transfer of the image data; generating and storing a plurality of passcodes indicative of the conversion that is to be performed; and outputting the image data is transferred via the data communication bus between the memory and the control unit a first time before the conversions by the at least two conversion units and a second time after competition of the conversions by the at least two conversion units.

28. Endo, however, discloses a working memory unit for storing input document data, and performing image data format conversion and transmission to a plurality of destinations (see Fig.2 (203,205), Fig.4, Col.3, Line 48-52 and Col.4, Line 38-48). Moil discloses an image processor for printing image data (see Fig. 1 and Col.4, Line 35-41), wherein the image processor includes a first conversion unit for converting image data into a format based on its initial compression format (see Fig. 1 (22) and Col.6, Line 31-37), a second conversion unit for converting the color format of the image data into a second color format (see Fig. 1 (33) and Col.7, Line 30-37), and a clock unit configured to provide synchronization between the control unit and the two conversion units for transfer of image data (see Fig. 1 (30,22,27,33), Col.5, Line 15-30, Col.5, Line 55-59 and Col.6, Line 4-18). Yasunobu discloses an electronic device for

Art Unit: 2625

converting image data into a suitable format for transmission (see Fig.1, Fig.3 and Col.4, Line 38-47), wherein the image data is transferred between the memory and the control unit a first time before the conversions by the at least two conversion units and a second time after completion of the conversions by the at least two conversion units (see Fig.2 (20,21, 23,27,32,33,34), Col.7, Line 2-10 and Col.7, Line 54 - Col.8, Line 3). [Note: The input image data is stored into the data storage unit 21 of Figure 2 via central controller 20 for image processing. The data conversion management unit 33 and the format converter 34 convert the input image data into the appropriate format and stores the image data back into data storage unit 21 before the image transmission process.]

29. Endo, Mori and Yasunobu are combinable because they are from the same field of endeavor, namely image data processing methods. At the time of the invention, it would have been obvious for one skilled in the art to include to Endo's method of converting image data the steps for selecting at least two conversion units in response to a notified type of conversion; supplying, from the control unit to the selected conversion units, a clock signal that provides synchronization for transfer of the image data; and outputting the image data to the communication bus after image data conversions by at least two data conversion units. The motivation would be to convert the image data into a suitable output format for printing in accordance to the type of processing that is to be performed with respect to the image data, and to regulate the transmission of image data to the image conversion units at a predetermined rate. The compression format and the color format of the image data would allow for the image data to be printed at a specific outputting device, based on the type of image data received from the input device. The synchronizing clock unit can ensure a steady flow of image data to the

Art Unit: 2625

conversions units for processing efficiency. It is further obvious for one skilled in the art to include the steps for transferring the image data via the data communication bus between the memory and the control unit a first time before the conversions by the at least two conversion units and a second time after completion of the conversions by the at least two conversion units. The motivation would be to store the processed image data into memory for image transmissions. The stored and processed image data could be used for retransmissions or transmission to another device, without having to repeat the conversion process on the image data. It is also obvious for one skilled in the art to include the step generating and storing a plurality of passcodes indicative of the conversion that is to be performed. The motivation would be to use a computer instruction codes for controlling the control unit to make the conversion unit selections.

30. Regarding **Claim 28**, Endo further discloses a step of notifying, by the control unit, the conversion request generating unit of a completion of the conversion of the image data (see Fig.10B (S1013,S1014) and Col.8, Line 14-22).

31. Claims 8-10 are rejected under 35 U.S.C. 103(a) as being unpatentable over Endo (US Patent 6,801,340 B 1) in view of Moil (US Patent 6,965,453 B 1), and in further view of Yasunobu (US Patent 7,046,394 B2), and in further view of Grosse et al. (US Patent 5,636,294).

32. Regarding **Claim 8**, Endo, Moil and Yasunobu teach the electronic device as described in Claim 1 but they fail to disclose wherein at least one of the conversion units includes an interruption unit configured to output an interruption signal to the control unit. Grosse, however, discloses an interruption unit configured to output an interruption signal to the control unit for

Art Unit: 2625

processing the image data at a predetermined size (see Fig. 15 (454,464,470) and Col. 15, Line 23-36).

33. Endo, Moil, Yasunobu and Grosse are combinable because they are from the same field of endeavor, namely image data processing systems. At the time of the invention, it would have been obvious for one skilled in the art to include to the conversion units an interruption unit configured to output an interruption signal to the control unit. The motivation would be to process the image data at a predetermined size and rate.

34. Regarding **Claim 9**, Grosse further discloses the interruption unit outputs the interruption signal in response to a completion of conversion of image data that is equal to a predetermined amount (see Fig.15 (454,464,470) and Col.15, Line 23-36).

35. Regarding **Claim 10**, Endo, Moil, Yasunobu and Grosse teach the interruption unit of Claim 8 but they fail to expressly disclose that the interruption unit outputs the interruption signal in response to a completion of conversion of image data that is equal in amount to one page of a print sheet. Grosse, however, teaches outputting the interruption signal in response to a completion of conversion of image data that is equal to a predetermined amount (see Fig.15(454,464,470) and Col. 15, Line 23-36). At the time of the invention, it would have been obvious for one skilled in the art to include to the interruption unit a means for outputs the interruption signal in response to a completion of conversion of image data that is equal in amount to one page of a print sheet. The motivation would be to process (compress) the image data one page data at a time, since the print data is processed (rasterized) in page by page basis.

Art Unit: 2625

36. Claims 3-4, 6-7 and 11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Endo (US Patent 6,801,340 B 1) in view of Mori (US Patent 6,965,453 B1), and in further view of Yasunobu (US Patent 7,046,394 B2), and in further view of Ohara (US Patent 7,072,060 B2).

37. Regarding **Claim 3**, Endo, Mori and Yasunobu teach the apparatus of Claim 1 but they fail to disclose wherein the control unit supplies to one of the conversion units a signal indicating that the image data being transferred is a sub-scan portion of the image data when the sub-scan portion of the image data is being transferred to one of the conversion units. Ohara, however, teaches an image data compression apparatus (see Fig.2 (108,113,115) and Col.5, Line 55 - Col.6, Line 12) wherein the main-scan lines and the sub-scan lines of the image data is read in and processed (see Fig.4A (303,306,308,321) and Col.7, Line 27-42). Ohara further teaches supplying a signal indicating that the image data being transferred and processed is either a sub-scan portion of the image data or a main-scan line portion of the image data (see Fig.4A (303,306,308,321) and Col.7, Line 43-46).

38. Endo, Mori, Yasunobu and Ohara are combinable are combinable because they are from the same field of endeavor, namely image data processing systems. At the time of the invention, it would have been obvious for one skilled in the art to include to Endo's device a mechanism for supplying to one of the conversion units a signal indicating that the image data being transferred is a sub-scan portion of the image data a main-scan line portion of the image data. The motivation would be to select the appropriate image data conversion engine for the scan line image data. The main-scan lines may require a particular image data conversion engine for processing the main-scan lines, while the sub-scan lines may require a another image data conversion engine that is different. The main-scan lines and sub-scan lines are likely to use

Art Unit: 2625

different compression methods and therefore, it would be beneficial to notify the conversion units which scan-line portion of the image data is being transmitted.

39. Regarding **Claim 4**, the rationale provided for the rejection of Claim 3 is incorporated herein.

40. Regarding **Claim 6**, Endo, Mori and Yasunobu teach the apparatus of Claim 1 but they fail to disclose wherein one of the conversion units supplies to the control unit a signal indicating that the image data being transferred is a sub-scan portion of the image data when the sub-scan portion of the converted image data is being transferred to the control unit. Ohara, however, teaches an image data compression apparatus (see Fig.2 (108,113,115) and Col.5, Line 55 - Col.6, Line 12) wherein the main-scan lines and the sub-scan lines of the image data is read in and processed (see Fig.4A (303,306,308,321) and Col.7, Line 27-42). Ohara further teaches supplying a signal indicating that the image data being transferred and processed is either a sub-scan portion of the image data or a main-scan line portion of the image data (see Fig.4A (303,306,308,321) and Col.7, Line 43-46).

41. At the time of the invention, it would have been obvious for one skilled in the art to include to Endo's device a mechanism for supplying to the control unit a signal indicating that the image data being transferred is either a sub-scan portion of the converted image data or the main-scan portion of the converted image data. The motivation would be to select the appropriate image data decompression engine for expanding the compressed image data. The main-scan lines and sub-scan lines are likely to use different compression methods. Therefore, it would be beneficial to notify the control units which scan-line portion of the converted image

Art Unit: 2625

data is being transmitted in order to send the scan-line portions of the image data to the appropriate decompression engines.

42. Regarding **Claim 7**, the rationale provided for the rejection of Claim 6 is incorporated herein.

43. Regarding **Claim 11**, Endo and Mori teach the device of Claim 8 but they fail to disclose wherein the interruption unit outputs the interruption signal in response to an error occurring during the conversion of the image data. Ohara, however, teaches an interruption unit for outputting the interruption signal in response to detecting the image data amount to be exceeding a limit, and routing the image data to a second compression engine to continue processing (see Fig.2 (108,113,115), Fig.6 (\$505,\$508,\$511) and Col.13, Line 1-24). At the time of the invention, it would have been obvious for one skilled in the art to include to the interruption unit a mechanism for outputting the interruption signal in response to an error occurring during the conversion of the image data. The motivation would be to discontinue the current conversion of the image data and to send a notification to the controller (or display) that an error has occurred.

Conclusion

44. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

45. A shortened statutory period for reply to this final action is set to expire **THREE MONTHS** from the mailing date of this action. In the event a first reply is filed within **TWO MONTHS** of the mailing date of this final action and the advisory action is not mailed until after the end of the **THREE-MONTH** shortened statutory period, then the shortened statutory period

Art Unit: 2625

will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

46. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Vu B. Hang whose telephone number is (571)272-0582. The examiner can normally be reached on Monday-Friday, 9:00am - 6:00pm.

47. If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David K. Moore can be reached on (571) 272-7437. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

48. Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Vu B. Hang/
Examiner, Art Unit 2625

/David K Moore/

Application/Control Number: 10/799,707

Page 23

Art Unit: 2625

Supervisory Patent Examiner, Art Unit 2625